GT5000

"Presenting" the GT5000 Series TTW ATM

Genmega introduces the GT5000 series ATM.

A high performance yet economical Through-The-Wall ATM solution with the look and feel of a full bank ATM.

Designed for wall or Kiosk installation, the GT5000 series makes new TTW installation or replacements a snap.

Built with the same compact modular components as your existing Genmega machines and engineered for easy installation and reliable operation.

The GT5000 includes high-end features like a 15" High Bright LCD which support custom advertisements and a 3-cassette cash dispenser with motorized cash presenter. A new Touch-Screen rear-service panel allows convenient and safe access for ATM Operators and Service personal.

The GT5000 series ATM is ADA compliant and Chip Card (EMV) ready, including a PCI / Interac certified encrypting PIN pad (EPP), a voice guidance system, and lighted action indicators (including lighted keypad).

Features of a high end Through-The-Wall ATM with the low maintenance and reliability that Genmega delivers makes this an excellent TTW solution.







(800) 363-9835 | sales@nationallink.com www.nationallink.com



www.genmega.com

Integrated Illuminated Topper Sign

High Visibility LED Sign Attract Customers

LCD Screen

15 inch color TFT-LCD Panel High bright LED backlight (800cd/m²) 1024 x 768 (XGA) Resolution

Printer

80mm/3" Receipt Printer 200DPI monographic printing

PIN Entry Device

16-key alphanumeric keypad PCI 3.0 / Interac Certified Triple-DES (TDES) compliant EPP

Rear Service Panel

7 inch color touch screen Backlit TFT LCD panel 800 x 480 Resolution

Communication

56Kb Internal Modem TCPIP Ethernet - SSL







CPU

Cortex-A8 CPU (800MHz) DDR2 256MB SRAM memory 512MB Flash Memory Windows CE 6.0

ADA

Voice Guidance Lighted Transaction Guidance Accessible Keypad Layout

Card Reader

DIP Style Magnetic Card Reader EMV - Optional

Security

UL291 Business Hours Vault Electronic Lock or Cencon (optional)

Cash Dispenser

Up to 3 x 1700 Note Removable Cassette Up to 3 x 2000 Note Removable Cassette Presenter module

Dimensions

Height = 56.7" Width = 24.1" Depth = 33.9" Weight = 570 lbs

Operating Environment

Temperature range: 40°F - 95°F Relative humidity: Non-condensing=15%-85%

Power Requirements

110/220 VAC ± 10%, 50/60 Hz, 145 Watts



